



PULSE

Ryko Solutions

The Pulse is Ryko Solutions' newest offering for customers looking for a value opportunity and want an economically designed touch free car wash that offers an equivalent wash quality of similar machines that are constructed for higher volume operations. Customers also looking to upgrade from self service bay type locations to capture more profit and improve their return on investment will also appreciate the attractive cost and revenue advancing options of this touch-free model that is packed with multiple value options.

pulse



PULSE

Ryko Solutions

Pulse Packages Components

Bronze

One Step PreSoak
Clear Coat
RykoNet II Arming
Simple Entrance Gantry Cover
25' Painted Steel, Floor Mounted Tracks
Stop/Go/Back-Up Light
Reverse Osmosis Ready
Reclaim Ready

Silver

Two Step PreSoak
Clear Coat
RykoNet II Arming
Simple Entrance Gantry Cover
25' Painted Steel, Floor Mounted Tracks
Stop/Go/Back-Up Light
Reverse Osmosis Ready
Reclaim Ready
Wax
Water Heater (Pump Bench)
Rust Inhibitor (Pump Stand)
Tire Chemical
Fixed Under Car

Gold

Two Step PreSoak
Clear Coat
RykoNet II Arming
Simple Entrance Gantry Cover
25' Painted Steel, Floor Mounted Tracks
Stop/Go/Back-Up Light
Reverse Osmosis Ready
Reclaim Ready
Wax
Water Heater (Pump Bench)
Rust Inhibitor (Pump Stand)
Tire Chemical
Tri Foam Wax
Fixed Under Car with Side Rocker Panel
Blasters or Oscillating Rocker Panel Blaster
Surface Sealant
Tire Chemical Sprayer

Additional Accessories

Auto Door Kit (Look or PES), Free Standing Dryer, 8 Segment Sign, Bay Buzzer, Spot Free Reverse Osmosis, Entrance Clearance Bar, 3 Message Entrance Sign, Front Facia Fiberglass Cover, Reclaim, 27' Painted Steel Tracks, Radius Stainless Steel Wall Mounts

Specifications

Building Requirements*	Minimum		Recommended	
	Standard	Metric	Standard	Metric
Bay Length 25' (7.6 m) track	27'	8.2 m	30'	9.1 m
Bay Length 27' (8.2 m) track	29'	8.8 m	32'	9.7 m
Bay Width	12' 8"	3.86 m	15' 6"	4.7 m
Bay Height 84" (213 cm)	10' 6"	3.05 m	12' 6"	3.8 m
Bay Height 90" (229 cm)	11'	3.35 m	12' 6"	3.8 m

	Minimum	Maximum
Electrical Requirements	208/230V 3 Phase, 60 HZ 90/80 AMPS Plus 120V 1 Phase, 20 AMPS OR 380/415V 3 Phase, 50 HZ with Neutral, 44 AMPS	
Recommended Water Supply	30 GPM (114 LPM)	
Air Requirements	3/8" (9.53 mm) ID line – 100 PSI (6.9 bar) at 9 SCFM flow	120 PSI (8.3 bar) at 9 SCFM flow

*Does not include space needed for off board dryer.

